

# IPCOM



ON-FARM

Supplementary unit that links Dinamica Generale indicators with the DTM™ Software on a PC network. Based on the Ethernet interface (IP address communication protocol) and WiFi connection.

## BENEFITS

- Secure yet reliable data processing with real time wireless communication
- Improved efficiency for large farms and companies that work with different machineries
- Enhanced communication performance (up to 1 km range)
- Increased time savings for routine data exchange operations

## FEATURES

- Open connectivity with real time wireless communication among Dinamica Generale devices
- IPcom™ proprietary interface developed by Dinamica Generale provides standard Wi-Fi access point
- IPcom™ includes a WiFi modem (100 m range) and the Ethernet port to connect the Dinamica Generale WiFi Antenna that covers up to 1 Km range (0.6 miles)
- Direct connection to the DG600 Slim Case, DG8000 and DG8000-IC.

## TECHNICAL DATA



**CABLE LENGTH**  
3 m



**INGRESS PROTECTION**  
IP 66 \*



**POWER SUPPLY**  
9-24 Vdc



**WEIGHT**  
850 g (1.9 lbs)



**WORKING TEMPERATURE**  
-40 / +65°C (-40 / +150°F)



**CASE DIMENSIONS**  
160x 80 x 160 mm (6.3 x 3 x 6.3 inches)



**RELATIVE HUMIDITY**  
5% to 95% (non-condensing)

## CONFIGURATION AND INSTALLATION:

