

# 2405 & 2410 Belt Conveyor/Feeder Specs

STANDARD Equipment		2405	2410
<b>Length</b>	Forward direction up to 100 ft. (30.48 m).	■	
	Forward direction up to 400 ft. (121.92 m).		■
<b>Frame</b>	Concave open bed, formed 14 ga. blue powder coated steel.	■	■
	6 1/2" (165 mm) depth, 26 3/4" (679 mm) width.	■	■
<b>Belt Width</b>	24" (610 mm)	■	■
<b>Belt</b>	Order as optional equipment.	■	■
<b>Belt Speed</b>	370 ft/min (112.8 m/min), 260 ft/min (79.2 m/min), 130 ft/min (39.6 m/min) or 65 ft/min (19.8 m/min), depending on drive selected.	■	
	325 ft/min (99.06 m/min), 240 ft/min (73.15 m/min), 120 ft/min (36.57 m/min) or 95 ft/min (29 m/min), depending on drive selected.		■
<b>Drive Pulley</b>	5" (127 mm) dia., crowned, steel, rubber lagged.	■	
	10" (254 mm) dia., crowned, steel, rubber lagged.		■
<b>Tail Pulley</b>	5" (127 mm) dia., finned, steel.	■	
	5 3/4" (146 mm) dia., finned, steel.		■
<b>Bearings</b>	Long-life, sealed, prelubricated, greasable.	■	■
<b>Belt Take-up</b>	Screw-type take-up at tail pulley.	■	■
<b>Drive Mount</b>	Order as optional equipment.	■	■
<b>Load Capacity</b>	Up to 209 ft <sup>3</sup> /min (5.91 m <sup>3</sup> /min), 3,700 lbs/min (1678 kg/min).	■	
	Up to 180 ft <sup>3</sup> /min (5.09 m <sup>3</sup> /min), 3,250 lbs/min (1474 kg/min).		■
<b>Span</b>	Up to 10' (3.04 m) between supports.	■	■
<b>Color</b>	Blue high-gloss polyester powder coat.	■	■
<b>Electrical Controls</b>	Customer supplied, except optional equipment.	■	■
<b>Assembly</b>	Conveyor supplied unassembled.	■	■
OPTIONAL Equipment		2405	2410
<b>Overall Lengths</b>	Conveyor lengths from 20' (6.1 m) to 100' (30.48 m) are possible.*	■	
	Conveyor lengths from 20' (6.1 m) to 400' (121.92 m) are possible.*		■
	<i>*Intermediate lengths are possible by field cutting.</i>		
<b>Belt</b>	Black, P.V.C. 120 COS, smooth or textured, standard & cold temp. Other belts available upon request.	■	■
<b>Drive Motors</b>	1 to 3 HP, 1 Ph. or 3 Ph.	■	
	3 to 7 1/2 HP, 1 Ph. or 3 Ph.		■
<b>Conveyor Supports</b>	Supports and mounting hardware available.	■	■
<b>Covers</b>	16 ga. powder coated in 10' (3.048 m) lengths.	■	■
<b>Loading Hoppers</b>	Funnels material into conveyor trough.	■	■
<b>Belt Wipers</b>	Blade for cleaning top of belts.	■	■
<b>Adjustable Decline</b>	Adjust 0° to 30°.	■	■
<b>Convey Sides</b>	Positions material and helps seal edges to prevent material under belt.	■	■
<b>Movable Plow</b>	1-way plow: for end charge feeder, belt travel in one direction only.	■	■
	1-way v-plow: for end charge feeder. For plowing granular material off both sides of belt simultaneously.	■	■
	2-way plow: use when plowing feed off each side, one side at a time.	■	■
<b>Plow Drive Control Box Assembly</b>	1 Ph., 60 Hz or 3 Phase, 50 or 60 Hz.	■	■
<b>Proximity Switch Assembly</b>	Use with plow drive control box to add additional lots or plow park feature. Includes proximity switch and cable.	■	■
<b>Tripper Assembly</b>	To trip 2-way plows right or left from a remote location.	■	■
<b>Tripper Assembly w/Controls</b>	To trip 2-way plows on each pass. Not electrically controlled.	■	■

## Optional:

### Plow Drive Control Box Assembly



### Includes:

- **Plow Drive Control Box**  
Available in: 1Ø or 3Ø, 230 V power, 50/60 Hz. Higher voltage option available.
  - Fiberglass enclosure
  - 3" black and white touch screen display
  - (2) operational modes: MANual and LOT
  - Capable of up to (10) configurable multi-lots
  - PARK feature
  - Large, red stop button - built-in safety feature
  - Built in tripper control
- **(2) proximity sensors** can accept up to (6) for multi-lot layouts
- **1 HP motor**



**CAUTION:** Never operate Patz equipment without all shields and guards in place. Safety is no accident. Before operating any piece of equipment, be sure to read and understand the operator's manual. This manual should be kept with the machine at all times. Additionally, make sure all safety shields and devices are functioning properly and are securely in place.



For some photos in this brochure, guards were removed for photographic purposes only to allow viewing of the equipment features. Before operating equipment, all guards must be in place. Because Patz continually improves and updates products, Patz reserves the right to change the construction of machines or attachments or any part thereof without incurring any obligation to make like changes on Patz machines, or attachments previously delivered. Specifications and prices subject to change without notice.

**Proven Performance You Can Count On!**  
**Patz Corporation**  
 917 Business 141, POB 7 • Pound, Wisconsin 54161-0007  
 Ph: (920) 897-2251 • Fax: (920) 897-2142  
 www.patzcorp.com • info@patzcorp.com

